

Redring[®] a custom designed optical shotgun sight

rearing

Redring[®] – the first custom designed optical shotgun sight in the world

Redring[®] is equally suited for hunting and sport shooting. It is designed for Over/Under, and Semi-automatic shotguns with a rib width ranging from 5 to 11.5 mm.

Redring[®] is designed, developed and manufactured in Sweden to the highest standards without compromise. It is so well designed that once mounted on the gun, it's ready to shoot without sight-in or calibration. With Redring[®] on the gun, many of the most common shooting problems have been solved. The result – safer, more enjoyable and controlled shooting.





Redring[®] – improves your shooting self-confidence

Redring® was a brilliant idea from the start. Today this idea has become a world-class product – designed, developed and manufactured in Sweden to the highest standards without compromise. It incorporates several unique functions: spot-metering of light, recoil absorbing rib mounts, and the red ring itself with USB compatibility. Redring® gives the shooter perfect aim and indicates when it's safe to shoot and when it's not. When the target looks right in relation to the ring, that's when it's time to shoot. The result is greater accuracy, more fun and more reliable hunting.

Parallax Free

Redring[®] enables the shooter to fire with both eyes open, irrespective of eye dominance. The open eyes principle improves the perceptual tendencies and helps the shooter to identify the target faster. Since Redring[®] is parallax free, what the shooter sees in the ring equals the target image, i.e., when the ring is right in relation to the target, the shot most certainly is a hit. The eye relief doesn't matter.

100% control

A correctly mounted gun and a correct sight alignment are essential to all shooters. Imaging the target in the correct way is probably the most crucial element. The initial target image and the firing image are critical in order to achieve a perfect shot. Redring[®] will help the shooter achieve the correct starting image of each shot. It's from this point the shooter starts the swing or movement towards the firing image. The firing image is individually adjusted to each shooters swing tempo. With Redring[®] the shooter will have almost 100% control over the whole shooting process from start to hit.



Unique functions

Spot-metering

Redring[®] has built-in intelligence, called spot metering, that reads the backlight in a diameter equivalent to more than double the ring diameter. An integrated processor momentarely adjusts the ring intensity to the prevailing light. Dark background = weaker ring. Bright background = stronger ring. The directed spot metering gives the shooter a great advantage in all types of hunting with varying lighting conditions, such as duck shooting in the sunrise. Light intensity can also be set manually.

The red ring

Another advantage of using the Redring[®] is that it also is an effective rangefinder. The size of the ring on the target equals the shot diameter/burst at 20 meters (65 feet). This gives the shooter an instant indication if the target is within shooting range or if it's too far away for a sure shot. When the ring looks right, pull the trigger. It surely improves the hit rate and reduces the risk of injuring the game.

Low mount with recoil absorption

Redring[®] is mounted free-floating directly on to the rib of the gun. It only takes a couple of minutes to mount and the sight is ready to use. No alterations or changes to the gun are necessary. As the lightweight sight is mounted low on the shotgun rib, it will not have any noticable effect on the balance of the gun. Redring[®] comes complete with recoil absorbing mounts for shotguns with a rib width ranging from 5 to 11.5 mm.

USB function

Redring[®] can be connected to your computer via a USB interface. This enables the shooter to register the equipment, log personalized statistics, select advanced settings, and receive periodic software upgrades from manufacturer. Go to www.redringsight.com/usb for instructions and downloading the necessary software.



Technical data

Battery:	AAAA 1.5V, Approx 300 h life. Redring® automatically shuts off after 4 hrs
Weight:	134 g (4.726oz) excluding mounts, 192 g (6.773oz) including mounts
Length:	
Width:	
Height:	
Material:	Anodised aluminium
Warranty:	



Redring AB Tärnvägen 15 • SE-475 40 Hönö • Gothenburg • Sweden Phone: +46 31 30 10 780

www.redringsight.com



Your local distributor/retailer: